SAFETY DATA SHEET	Page : 1 / 15
	Revision nr : 1.0
	Issue date : 15/09/2021
DLP Craftsman Resin	Supersedes:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : DLP Craftsman Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category : Consumer use

Use of the substance/mixture : Resin

3D printer filaments

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Shenzhen Anycubic Technology Co., Ltd
12-13th floor, Building #3B, Vanke Times Square, No.85 Longcheng Avenue, Longcheng Street
518000 Longgang District, Shenzhen, Guangdong - China
T 18682218561
sunxianping@anycubic.com

1.4. Emergency telephone number

Emergency number : 18682218561

Only available during office hours.

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, 24/7, healthcare professionals only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2 H315
Eye Irrit. 2 H319
Skin Sens. 1 H317
Repr. 2 H361f
STOT SE 3 H335
Aquatic Chronic 2 H411

Full text of H- and EUH-statements: see section 16

SAFETY DATA SHEET	Page : 2 / 15
	Revision nr : 1.0
	Issue date : 15/09/2021
DLP Craftsman Resin	Supersedes :

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :







Signal word : Warning

Contains : 2-Oxepanone, homopolymer, 2-[(1-oxo-2-propen-1-yl)oxy]ethyl ester,

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Hazard statements (CLP) : H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H361f - Suspected of damaging fertility.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children. P261 - Avoid breathing vapours.

P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, eye protection, face

protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P391 - Collect spillage. P405 - Store locked up.

P501 - Dispose of contents and container to an approved waste disposal

plant.

2.3. Other hazards

Other hazards : Results of PBT and vPvB assessment : Not applicable.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-Oxepanone, homopolymer, 2-[(1-oxo-2-propen-1-yl)oxy]ethyl ester	(CAS-No.) 110489-05-9 (EC-No.) 600-970-0	30 – 50	Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335

SAFETY DATA SHEET	Page : 3 / 15
	Revision nr : 1.0
	Issue date : 15/09/2021
DLP Craftsman Resin	Supersedes :

Pentaerythritol, ethoxylated, esters with acrylic acid	(CAS-No.) 51728-26-8 (EC-No.) 500-111-9	10 – 25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 2, H411
Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega[(1-oxo-2-propen-1-yl)oxy]-	(CAS-No.) 64401-02-1 (EC-No.) 613-584-2	20 – 25	Aquatic Chronic 2, H411
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	(CAS-No.) 75980-60-8 (EC-No.) 278-355-8 (EC Index) 015-203-00-X	2 – 10	Repr. 2, H361f

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice : First aider: Pay attention to self-protection!. Concerning personal protective

equipment to use, see section 8. Never give anything by mouth to an

unconscious person. In case of doubt or persistent symptoms, consult always a

physician. Show this safety data sheet to the doctor in attendance.

Inhalation : Remove casualty to fresh air and keep warm and at rest. Give oxygen or

artificial respiration if necessary. In case of doubt or persistent symptoms,

consult always a physician.

Skin contact : Remove contaminated clothing and shoes. Gently wash with plenty of soap

and water. In case of doubt or persistent symptoms, consult always a

physician.

Eyes contact : Rinse immediately carefully and thoroughly with eye-bath or water. Remove

contact lenses, if present and easy to do. Continue rinsing. In case of doubt or

persistent symptoms, consult always a physician.

Ingestion : Rinse mouth thoroughly with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation : May cause respiratory irritation. The following symptoms may occur: Dizziness.

Drowsiness. Cough. Irritation of the nasal mucous membranes.

Skin contact : May cause an allergic skin reaction. Causes skin irritation. The following

symptoms may occur: Redness, pain.

Eyes contact : Causes serious eye irritation. The following symptoms may occur: Redness,

pain.

Ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Chronic symptoms : Suspected of damaging fertility.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : carbon dioxide (CO2), powder, alcohol-resistant foam, water spray.

Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Combustible. Heating will cause a rise in pressure with a risk of bursting.

Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Can form explosive

mixture with air.

Hazardous decomposition products in

case of fire

: Carbon oxides (CO, CO2).

SAFETY DATA SHEET	Page : 4 / 15
	Revision nr : 1.0
	Issue date : 15/09/2021
DLP Craftsman Resin	Supersedes :

5.3. Advice for firefighters

Firefighting instructions : Evacuate area. Use water spray or fog for cooling exposed containers. Contain

the extinguishing fluids by bunding. Prevent fire fighting water from entering

the environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-

contained breathing apparatus.

Other information : Do not allow run-off from fire-fighting to enter drains or water courses.

Dispose of waste in accordance with environmental legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

For non-emergency personnel

: Evacuate unnecessary personnel. Keep upwind. Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Wear recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure equipment is adequately earthed. Use explosion-proof equipment. Use only non-sparking tools.

6.1.2. For emergency responders

For emergency responders

: Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Stop leak if safe to do so. Dam up the liquid spill. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Take any precaution to avoid mixing with Incompatible materials, Refer to Section 10 on Incompatible Materials. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Avoid release to the environment. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools.

SAFETY DATA SHEET	Page: 5 / 15 Revision nr: 1.0
	Issue date : 15/09/2021
DLP Craftsman Resin	Supersedes :

Hygiene measures

: Keep good industrial hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a dry, cool and well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10. Bund storage facilities to prevent soil and water pollution in the event of spillage.

Heat and ignition sources

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Special rules on packaging

: Tactile warning. Containers which are opened should be properly resealed and kept upright to prevent leakage.

: Keep only in the original container.

Packaging materials

7.3. Specific end use(s)
Resin. 3D printer filaments.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information

: Recommended monitoring procedures :. Personal air monitoring. Room air monitoring

8.2. Exposure controls

Engineering measure(s)

: Organisational measures to prevent /limit releases, dispersion and exposure.

See Section 7 for information on safe handling. Use only outdoors or in a wellventilated area. Take precautionary measures against static discharges. Ensure
equipment is adequately earthed.

Personal protective equipment

The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hand protection

: Wear chemically resistant gloves (tested to EN374) . Suitable material: Not determined. Thickness: Not determined. Breakthrough time: Not determined. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Eye protection

: Use suitable eye protection (EN166): goggles. Safety glasses

Body protection

: Wear suitable protective clothing

Respiratory protection

: In case of insufficient ventilation, wear suitable respiratory equipment. Half-face mask (DIN EN 140). full face mask (DIN EN 136). Filter type: ABEK (EN141). The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)

Thermal hazard protection

: Not required for normal conditions of use. Use dedicated equipment.

Environmental exposure controls

: Avoid release to the environment. Comply with applicable Community

environmental protection legislation.

Consumer exposure controls

: Avoid contact with skin, eyes and clothing. Avoid contact during pregnancy/while

nursing.

SAFETY DATA SHEET	Page : 6 / 15
	Revision nr : 1.0
	Issue date : 15/09/2021
DLP Craftsman Resin	Supersedes :

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Colour : White.
Odour : odourless.

Odour threshold : No data available pH : No data available Relative evaporation rate (butylacetate=1) : No data available Melting / freezing point : No data available Freezing point : No data available

Initial boiling point and boiling range : $238 \, ^{\circ}\text{C}$ Flash point : $90 \, ^{\circ}\text{C}$ Auto-ignition temperature : $252 \, ^{\circ}\text{C}$

Decomposition temperature : No data available
Flammability (solid, gas) : Not applicable,liquid
Vapour pressure : No data available
Vapour density : No data available
Relative density : No data available

Solubility : Insoluble in water. Soluble in ethanol.

Partition coefficient n-octanol/water : No data available Kinematic viscosity : 102 cPs (40 °C) Dynamic viscosity : No data available

Explosive properties : Not applicable. The study does not need to be conducted because there are

no chemical groups associated with explosive properties present in the

molecule.

Oxidising properties : Not applicable. The classification procedure needs not to be applied because

there are no chemical groups present in the molecule which are associated

with oxidising properties.

Explosive limits No data available Particle size : Not applicable Particle size distribution : Not applicable Particle shape : Not applicable Particle aspect ratio : Not applicable Particle aggregation state : Not applicable Particle agglomeration state : Not applicable Particle specific surface area : Not applicable Particle dustiness : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

SAFETY DATA SHEET	Page : 7 / 15
	Revision nr : 1.0
	Issue date : 15/09/2021
DLP Craftsman Resin	Supersedes :

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Combustible. Reference to other sections: 10.4 & 10.5.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. See Section 7 for information on safe handling.

10.5. Incompatible materials

Strong oxidizing agents. See Section 7 for information on safe handling.

10.6. Hazardous decomposition products

Reference to other sections 5.2.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

Pentaerythritol, ethoxylated, esters with acrylic acid (51728-26-8)		
LD50/dermal/rat	> 2000 mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)		
LD50/dermal/rat	> 2000 mg/kg	
Skin corrosion/irritation	: Causes skin irritation.	
4	pH: No data available	
Serious eye damage/irritation	: Causes serious eye irritation.	
	pH: No data available	
Respiratory or skin sensitisation	: May cause an allergic skin reaction.	
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)	
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)	
Reproductive toxicity	: Suspected of damaging fertility.	
STOT-single exposure	: May cause respiratory irritation.	
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)	
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)	
DLP Craftsman Resin		

Aspiration nazard	: Not classified (Based on available data, the classification criteria are not met)	
DLP Craftsman Resin		
Kinematic viscosity	102 mm ² /s (40 °C)	
Other adverse effects	: Suspected of damaging fertility.	
Other information	: Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.	

SAFETY DATA SHEET	Page: 8 / 15
	Revision nr : 1.0
	Issue date : 15/09/2021
DLP Craftsman Resin	Supersedes :

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

11.2.2 Other information

Other adverse effects : Suspected of damaging fertility.

Other information : Symptoms related to the physical, chemical and toxicological

characteristics, For further information see section 4

SECTION 12: Ecological information

12.1. Toxicity

Environmental properties : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment,

short-term (acute)

Hazardous to the aquatic environment,

long-term (chronic)

: Not classified

: Toxic to aquatic life with long lasting effects.

Pentaerythritol, ethoxylated, esters with acry	lic acid (51728-26-8)
LC50 - Fish [1]	1,76 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])

12.2. Persistence and degradability

DLP Craftsman Resin	
Persistence and degradability	No additional information available.

12.3. Bioaccumulative potential

DLP Craftsman Resin		
Partition coefficient n-octanol/water	No data available	
Bioaccumulative potential	No additional information available.	

12.4. Mobility in soil

DLP Craftsman Resin	
Mobility in soil	No data available

12.5. Results of PBT and vPvB assessment

DLP Craftsman Resin	
Results of PBT assessment	Not applicable

SAFETY DATA SHEET	Page : 9 / 15
	Revision nr : 1.0
	Issue date : 15/09/2021
DLP Craftsman Resin	Supersedes :

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

12.7. Other adverse effects

Other adverse effects : No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations

: Avoid release to the environment. Dispose of empty containers and wastes safely. See Section 7 for information on safe handling. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations. Packaging contaminated by the product: Do not pierce or burn, even after use. Never use pressure to empty container.

European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC)

: This material and its container must be disposed of as hazardous waste Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

In accordance with ADR / RID / IMDG / IATA / ADN					
ADR	IMDG	IATA	ADN	RID	
<u>14.1. UN number</u>					
3082	3082	3082	3082	3082	
14.2. UN proper ship	ping name				
ENVIRONMENTALLY	ENVIRONMENTALLY	Environmentally	ENVIRONMENTALLY	ENVIRONMENTALLY	
HAZARDOUS	HAZARDOUS	hazardous substance,	HAZARDOUS	HAZARDOUS	
SUBSTANCE, LIQUID,	SUBSTANCE, LIQUID,	liquid, n.o.s.	SUBSTANCE, LIQUID,	SUBSTANCE, LIQUID,	
N.O.S. (Poly(oxy-1,2-	N.O.S. (Poly(oxy-1,2-	(Poly(oxy-1,2-	N.O.S. (Poly(oxy-1,2-	N.O.S. (Poly(oxy-1,2-	
ethanediyl),	ethanediyl),	ethanediyl),	ethanediyl),	ethanediyl),	
.alpha.,.alpha.'-[(1-	.alpha.,.alpha.'-[(1-	.alpha.,.alpha.'-[(1-	.alpha.,.alpha.'-[(1-	.alpha.,.alpha.'-[(1-	
methylethylidene)di-	methylethylidene)di-	methylethylidene)di-	methylethylidene)di-	methylethylidene)di-	
4,1-	4,1-	4,1-	4,1-	4,1-	
phenylene]bis[.omega	phenylene]bis[.omega	phenylene]bis[.omega	phenylene]bis[.omega	phenylene]bis[.omega	
[(1-oxo-2-propen-1-	[(1-oxo-2-propen-1-	[(1-oxo-2-propen-1-	[(1-oxo-2-propen-1-	[(1-oxo-2-propen-1-	
yl)oxy]-;	yl)oxy]- ;	yl)oxy]- ;	yl)oxy]- ;	yl)oxy]- ;	
Pentaerythritol,	Pentaerythritol,	Pentaerythritol,	Pentaerythritol,	Pentaerythritol,	
ethoxylated, esters	ethoxylated, esters	ethoxylated, esters	ethoxylated, esters	ethoxylated, esters	
with acrylic acid)	with acrylic acid)	with acrylic acid)	with acrylic acid)	with acrylic acid)	
Transport document de	Transport document description				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082	
ENVIRONMENTALLY	ENVIRONMENTALLY	Environmentally	ENVIRONMENTALLY	ENVIRONMENTALLY	
HAZARDOUS	HAZARDOUS	hazardous substance,	HAZARDOUS	HAZARDOUS	
SUBSTANCE, LIQUID,	SUBSTANCE, LIQUID,	liquid, n.o.s.	SUBSTANCE, LIQUID,	SUBSTANCE, LIQUID,	
N.O.S. (Poly(oxy-1,2-	N.O.S. (Poly(oxy-1,2-	(Poly(oxy-1,2-	N.O.S. (Poly(oxy-1,2-	N.O.S. (Poly(oxy-1,2-	
ethanediyl),	ethanediyl),	ethanediyl),	ethanediyl),	ethanediyl),	
.alpha.,.alpha.'-[(1-	.alpha.,.alpha.'-[(1-	.alpha.,.alpha.'-[(1-	.alpha.,.alpha.'-[(1-	.alpha.,.alpha.'-[(1-	

ADR	IMDG	IATA	ADN	RID
methylethylidene)di-	methylethylidene)di-	methylethylidene)di-	methylethylidene)di-	methylethylidene)di-
4,1-	4,1-	4,1-	4,1-	4,1-
phenylene]bis[.omega	phenylene]bis[.omega	phenylene]bis[.omega	phenylene]bis[.omega	phenylene]bis[.omega
[(1-oxo-2-propen-1-	[(1-oxo-2-propen-1-	[(1-oxo-2-propen-1-	[(1-oxo-2-propen-1-	[(1-oxo-2-propen-1-
yl)oxy]- ;	yl)oxy]- ;	yl)oxy]-;	yl)oxy]- ;	yl)oxy]- ;
Pentaerythritol,	Pentaerythritol,	Pentaerythritol,	Pentaerythritol,	Pentaerythritol,
ethoxylated, esters	ethoxylated, esters	ethoxylated, esters	ethoxylated, esters	ethoxylated, esters
with acrylic acid), 9,	with acrylic acid), 9,	with acrylic acid), 9, III	with acrylic acid), 9, III	with acrylic acid), 9, III
III, (-)	III, MARINE			
	POLLUTANT			
14.3. Transport haza	rd class(es)			
9	9	9	9	9
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the	Dangerous for the	Dangerous for the	Dangerous for the	Dangerous for the
environment : Yes	environment : Yes	environment : Yes	environment : Yes	environment : Yes
	Marine pollutant : Yes	7		
No supplementary information available				

14.6. Special precautions for user

Special precautions for user : No data available

- Overland transport

Classification code (ADR) : M6

Special provisions : 274, 335, 375, 601

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container : T4

instructions (ADR)

Portable tank and bulk container

special provisions (ADR)

: TP1, TP29

Tank code (ADR) : LGBV

Vehicle for tank carriage : AT

Transport category (ADR) : 3

Special provisions for carriage - : V12

Packages (ADR)

Special provisions for carriage - Loading, unloading and handling

(ADR)

Hazard identification number (Kemler:

No.)

90

CV13

Orange plates : 90

Tunnel restriction code : EAC code : •3Z

- Transport by sea

Special provisions (IMDG) : 274, 335, 969

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : LP01, P001

Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A

- Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity : 30kgG

(IATA)

PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

- Inland waterway transport

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP
Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1

SAFETY DATA SHEET	Page: 12 / 15
	Revision nr : 1.0
	Issue date : 15/09/2021
DLP Craftsman Resin	Supersedes :

Mixed packing provisions (RID) : MP19
Portable tank and bulk container : T4

instructions (RID)

Portable tank and bulk container special : TP1, TP29

provisions (RID)

Tank codes for RID tanks (RID) : LGBV
Transport category (RID) : 3
Special provisions for carriage - : W12

Packages (RID)

Special provisions for carriage - : CW13, CW31

Loading, unloading and handling (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Code: IBC : No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	DLP Craftsman Resin; Pentaerythritol, ethoxylated, esters with acrylic acid; 2- Oxepanone, homopolymer, 2-[(1-oxo-2- propen-1-yl)oxy]ethyl ester
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	DLP Craftsman Resin; Pentaerythritol, ethoxylated, esters with acrylic acid; Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega[(1-oxo-2-propen-1-yl)oxy]-

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

France

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
4511.text	Dangereux pour l'environnement aquatique de catégorie chronique 2.		
4511.1	La quantité totale susceptible d'être présente dans l'installation étant : 1. Supérieure ou égale à 200 t Quantité seuil bas au sens de l'article R. 511-10 : 200 t. Quantité seuil haut au sens de l'article R. 511-10 : 500 t.	A	1
4511.2	La quantité totale susceptible d'être présente dans l'installation étant : 2. Supérieure ou égale à 100 t mais inférieure à 200 t Quantité seuil bas au sens de l'article R. 511-10 : 200 t. Quantité seuil haut au sens de l'article R. 511-10 : 500 t.	DC	

SAFETY DATA SHEET	Page: 13 / 15
	Revision nr : 1.0
	Issue date : 15/09/2021
DLP Craftsman Resin	Supersedes :

Germany

Regulatory reference : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

: LGK 10 - Combustible liquids German storage class (LGK)

: Listed in the 12. BlmSchV (Annex I) under: 1.3.2 Hazardous Incident Ordinance (12.

BImSchV) Quantity threshold for operational area under § 1 para. 1

> Sentence 1: 200000 kg Sentence 2: 500000 kg

Netherlands

Waterbezwaarlijkheid : categorie Z(1) - niet-afbreekbare stoffen met gevaarlijke eigenschappen voor

mens en milieu (carcinogeniteit/ mutageniteit/ reprotoxiciteit/ bioacumulerend

vermogen/ toxiciteit of persistentie)

SZW-lijst van kankerverwekkende

stoffen

: None of the components are listed

SZW-lijst van mutagene stoffen

SZW-lijst van reprotoxische stoffen -

Borstvoeding

: None of the components are listed

: None of the components are listed

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

: Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide is listed

SZW-lijst van reprotoxische stoffen -

Ontwikkeling

: None of the components are listed

Denmark

Class for fire hazard : Class III-1 Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency

management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct

contact with the product

15.2. Chemical safety assessment

Not applicable

SECTION 16: Other information

Abbreviations and acronyms:

ABM = Algemene beoordelingsmethodiek
ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods Code LEL = Lower Explosive Limit/Lower Explosion Limit
UEL = Upper Explosion Limit/Upper Explosive Limit REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
BTT = Breakthrough time (maximum wearing time)
DMEL = Derived Minimal Effect level
DNEL = Derived No Effect Level

SAFETY DATA SHEET	Page: 14 / 15
	Revision nr : 1.0
	Issue date : 15/09/2021
DLP Craftsman Resin	Supersedes :

EC50 = Median Effective Concentration
EL50 = Median effective level
ErC50 = EC50 in terms of reduction of growth rate
ErL50 = EL50 in terms of reduction of growth rate
EWC = European waste catalogue
LC50 = Median lethal concentration
LD50 = Median lethal dose
LL50 = Median lethal level
NA = Not applicable
NOEC = No observed effect concentration
NOEL: no-observed-effect level
NOELR = No observed effect loading rate
NOAEC = No observed adverse effect concentration
NOAEL = No observed adverse effect level
N.O.S. = Not Otherwise Specified
OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
PNEC = Predicted No Effect Concentration
Quantitative structure-activity relationship (QSAR)
STOT = Specific Target Organ Toxicity
TWA = time weighted average
VOC = Volatile organic compounds
WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

Sources of key data used to compile the : ECHA (European Chemicals Agency). LOLI. Supplier information.

datasheet Training advice

: Training staff on good practice. Manipulations are to be done only by qualified

and authorised persons.

Other information

: Classification - Assessment method: CLP Calculation method (Article 9). Physicochemical hazard assessment: Information given is based on tests on the mixture itself.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility.
H411	Toxic to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Classification according to Regulation (EC) No. 1272/2008 [CLP] Labelling according to Regulation (EC) No. 1272/2008 [CLP]

SAFETY DATA SHEET	Page : 15 / 15
	Revision nr : 1.0
	Issue date : 15/09/2021
DLP Craftsman Resin	Supersedes :

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.